

# C-LINE

# TITAN

PI 255HC - PI 245HC



**Electro-hydraulic two post lifts with top connections**

Possibility of installation in symmetrical or asymmetric version



## Description

Electro-hydraulic two post lifts with top connections. Possibility of installation in **symmetrical** or **asymmetric** version.


Realignment of the two carriages using metal cables that guarantee excellent synchronisation.

**Standard height of two-post connection: 4,050 mm.**

Available versions (with optional column extension set):

- **V**: Specific for vans (Height of two-post connection: 4,620 mm).

- **XV**: Specific for vans and very high vehicles, extra-high version (Height of two-post connection: 5,220 mm).



**Internally reinforced column structure** for little bending and internal cable guiding.



**Electro magnet safety release 24V**



Rubber door protections.  
**Toothed sector arm rotation stop system**



Four **three-section symmetrical arms**

## Technical data

TITAN	PI 255HC	PI 245HC
Lift capacity	<b>5500 kg</b>	<b>4500 kg</b>
Lifting time	<b>45 s</b>	<b>45 s</b>
Motor	<b>400/230V-3kW-3ph-50 Hz</b>	<b>400/230V-3kW-3ph-50 Hz</b>
Lift max. lifting height	<b>2080 mm</b>	<b>2080 mm</b>
Max. locking position	<b>1957-2037 mm</b>	<b>1957-2037 mm</b>
Lift minimum height	<b>100 mm</b>	<b>100 mm</b>
Height connection	<b>4050/4620/5520 mm</b>	<b>4050/4620/5520 mm</b>

## Supplied accessories

- Safety stop-bar included as standard.
- Two set of extension pads.

## Optional



**A** - Column extension set

**B** - **8-43300021** Set of 4 extension for pads, H=35 mm

**C** - **8-43300014** Set of 4 extension for pads, H=80 mm

**D** - **8-43300015** Set of 4 extension for pads, H=140 mm

**E** - **8-43300016** Set of 4 adapters for Mercedes Sprinter

## Dimensions

